



ARTISAN®

Graffiti Remover

DESCRIPTION

Artisan Graffiti Remover is a V.O.C. compliant graffiti remover for use on surfaces coated with our 2-part barrier coating and other permanent barrier coatings. Artisan is a water rinseable remover. Artisan will dissolve, suspend and remove imbedded markings, defacements and adhesive from surfaces treated with Artisan 2-part barrier coating.

Artisan does not contain any chlorinated solvents, aromatic solvents, NMP, caustics or acids.

USES

In addition to using on crosslinked anti-graffiti barriers, Artisan can also be used on polished stone, glazed brick, painted block, manufactured stone, general masonry, ceramic, porcelain, fiberglass, non-anodized metal, stainless, glass, plastics and painted surfaces for the removal of graffiti. Artisan works best on smooth surfaces and those treated with one of our anti-graffiti barrier coatings. This product is not effective on porous surfaces.

PREPARATION

Test to determine compatibility, desired results and dwell time before general use. For best results, test a solution on an inconspicuous area before general use. Protect all other surfaces that this product is not intended for use.

PROPERTIES

Appearance	Clear to amber liquid
Odor	Slight solvent
Flash Point	>200 degrees F (c.c.)
V.O.C.	< 5%
lbs/gallon	8.0 - 8.2

APPLICATION

Do not dilute Artisan Graffiti Remover. Apply onto a dry surface, using a brush, roller or sprayer. Let stand for five minutes. Lightly agitate surface and rinse thoroughly. Some surfaces may require a second application. If applying onto an anti-graffiti treatment, wait until surface is completely dry and free of any remover residue. If applying onto our Artisan 2-part barrier coating, the coating must be allowed to cure for 5-7 days after application.

PACKAGED

Artisan is available gallons (2/case), 5 gallon pails and 55 gallon drums.

STORAGE AND SHELF LIFE

Store in a cool, dry room. Keep away from heat, sparks and flame. The shelf life for Artisan is indefinite in closed containers. Read MSDS before use.

DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.

STORAGE AND SHELF LIFE

Store in a cool dry room in original, closed containers. Keep away from acid and alkaline products.

TRANSPORTATION

Not regulated by the U.S. Department of Transportation for ground shipments.





Product Information

SAFETY AND HANDLING

For specific information, please refer to the material safety data sheet. Wear chemical resistant gloves, apron, footwear and goggles. Refer to product label and material safety data sheet for complete safety information.

Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. Get immediate medical attention. In case of contact with skin, wash with soap and water. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL: Absorb with inert material and dispose of properly. **KEEP OUT OF REACH OF CHILDREN.** Refer to Material Safety Data Sheet available for further safety and handling information.

WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, or can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc's liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.

